

## The ultimate in Low-Level Powered Access

Push into position, step in, press a button.

**Simple. Safe. Efficient.**

At JLG we believe safety is paramount. In line with the JLG range, the 830 has Auto-Lok wheels on elevation, as standard.

With a 2.5m platform height and 4.5m working height, the heavy-duty 830 maximises platform size whilst minimising working footprint, giving the operator more room to work in confined areas.

**Typical applications and users:** 830 maximizes platform size within a small footprint, ideal for users where the workspace is congested; second fix M&E work, busy retail refitting, simple spot work, new construction or maintenance.



### Key Features

- 4.5m working height
- Low platform entry height only 360mm
- Only 1.19m x 0.75m working footprint
- Passes easily through single doorways
- Large 1.0m x 0.73m platform size, gives the user more room to work
- Heavy duty Auto-Lok wheels on elevation

### **PUSH AROUND**

Indoor use\*

**Working Height:** 4.5 m

**Applications:** 2nd Fix. Spot Work. Pipe & Ductwork. M&E. Shopfitting. Retail.

Largest platform size in class;  
small working footprint.

# Model 830P

LOW-LEVEL ACCESS

## Specifications

### OPERATING DIMENSIONS

Working height:	4.50m
Maximum platform height:	2.50m
Closed platform height:	0.36m
Platform dimensions:	1.00m x 0.73m
Working footprint:	1.19m x 0.75m
Safe working load:	200kg (1 person plus tools)

### POWER OPTIONS

Power:	12V D.C. Battery.
Controls:	Simple push button heavy duty pendant controls for ground and platform.
Construction:	Heavy duty fabricated steel superstructure and 2 stage mast with Ultra-Glide technology. Tough, powder coated finish.
Safety:	Full fail-safe hydraulic circuit. Auto-Lok wheels.
Options:	110V or 230V mains power. Tilt alarm with auto cut-out. Protective storage cover.

### CLOSED DIMENSIONS

Length:	1.195m
Width:	0.75m
Height:	1.56m
Weight:	285kg

## Safety features

- Hydraulic circuit complete with check valve on lift cylinder
- Improved heavy-duty Auto-Lok wheels on elevation provide secure base
- Emergency descent from ground level
- Audible ascent and descent drive alarm



## IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.

# JLG®

**JLG EMEA BV**

Polaris Avenue 63  
2132 JH Hoofddorp  
The Netherlands  
Tel: +31 (0)23 565 5665  
Fax: +31 (0)23 557 3750  
[www.jlg.com](http://www.jlg.com)

**An Oshkosh Corporation Company**