

C9 ACERT
 240 ekW/ 300 kVA/ 50 Hz/ 1500 rpm/ 400 V/ 0.8 Power Factor

Rating Type: PRIME

Fuel Strategy: LOW FUEL CONSUMPTION



C9 ACERT
 240 ekW/ 300 kVA
 50 Hz/ 1500 rpm/ 400 V

Image shown may not reflect actual configuration

Metric English

Package Performance		
Genset Power Rating with Fan @ 0.8 Power Factor	240 ekW	
Genset Power Rating	300 kVA	
Aftercooler (Separate Circuit)	N/A	N/A

Fuel Consumption		
100% Load with Fan	62.5 L/hr	16.5 gal/hr
75% Load with Fan	47.3 L/hr	12.5 gal/hr
50% Load with Fan	33.8 L/hr	8.9 gal/hr
25% Load with Fan	20.6 L/hr	5.5 gal/hr

Cooling System ¹		
Engine Coolant Capacity	13.9 L	3.7 gal

Inlet Air		
Combustion Air Inlet Flow Rate	16.3 m ³ /min	575.5 cfm
Max. Allowable Combustion Air Inlet Temp	43 ° C	109 ° F

Exhaust System		
Exhaust Stack Gas Temperature	547.7 ° C	1017.9 ° F
Exhaust Gas Flow Rate	47.2 m ³ /min	1666.9 cfm
Exhaust System Backpressure (Maximum Allowable)	10.0 kPa	40.0 in. water



C9 ACERT
240 kW/ 300 kVA/ 50 Hz/ 1500 rpm/ 400 V/ 0.8 Power Factor

Rating Type: PRIME

Fuel Strategy: LOW FUEL CONSUMPTION

Heat Rejection		
Heat Rejection to Jacket Water	109 kW	6212 Btu/min
Heat Rejection to Exhaust (Total)	217 kW	12315 Btu/min
Heat Rejection to Aftercooler	44 kW	2488 Btu/min
Heat Rejection to Atmosphere from Engine	25 kW	1433 Btu/min
Heat Rejection to Atmosphere from Generator	16 kW	887 Btu/min

Alternator²	
Motor Starting Capability @ 30% Voltage Dip	748 skVA
Current	433 amps
Frame Size	LC5014L
Excitation	SE
Temperature Rise	125 ° C

Emissions (Nominal)³		
NOx	3200.3 mg/Nm ³	6.7 g/hp-hr
CO	809.8 mg/Nm ³	1.7 g/hp-hr
HC	15.1 mg/Nm ³	0.0 g/hp-hr
PM	24.4 mg/Nm ³	0.1 g/hp-hr

DEFINITIONS AND CONDITIONS

1. For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.
2. UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40° C ambient per NEMA MG1-32.
3. Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77° F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

C9 ACERT
240 ekW/ 300 kVA/ 50 Hz/ 1500 rpm/ 400 V/ 0.8 Power Factor

Rating Type: PRIME

Fuel Strategy: LOW FUEL CONSUMPTION

Applicable Codes and Standards:

AS1359, CSA C22.2 No100-04, UL142,UL489, UL869, UL2200,
NFPA37, NFPA70, NFPA99, NFPA110, IBC, IEC60034-1, ISO3046, ISO8528,
NEMA MG1-22,NEMA MG1-33, 2006/95/EC, 2006/42/EC, 2004/108/EC.

Note: Codes may not be available in all model configurations. Please consult your local Cat Dealer representative for availability.

PRIME:Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated ekW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions

Fuel Rates are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

www.Cat-ElectricPower.com

Performance No.: EM1033-00

Feature Code: C09DE1S

Generator Arrangement: 4692279

Date: 10/22/2015

Source Country: U.K.

The International System of Units (SI) is used in this publication. CAT, CATERPILLAR, their respective logos, ADEM, EUI, S•O•S, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.