



Image shown may not reflect actual package.

## STANDBY

**1400 ekW 1750 kVA  
50 Hz 1500 rpm 400 Volts**

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

## FEATURES

### FUEL/EMISSIONS STRATEGY

- Low Emissions

### DESIGN CRITERIA

- The generator set accepts 100% rated load in one step per NFPA 110 and meets ISO 8528-5 transient response.

### FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

### SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

### WORLDWIDE PRODUCT SUPPORT

- Cat dealers provide extensive post sale support including maintenance and repair agreements
- Cat dealers have over 1,800 dealer branch stores operating in 200 countries
- The Cat® S•O•S<sup>SM</sup> program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

### CAT 3512B-HD TA DIESEL ENGINE

- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke-cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight

### CAT SR5 GENERATOR

- Matched to the performance and output characteristics of Cat engines
- Industry leading mechanical and electrical design
- Industry leading motor starting capabilities
- High Efficiency

### CAT EMCP 3 SERIES CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway

# STANDBY 1400 kW 1750 kVA

50 Hz 1500 rpm 400 Volts



## FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"> <li>• Single element canister type air cleaner</li> <li>• Service indicator</li> </ul>	<input type="checkbox"/> Dual element & heavy duty air cleaners <input type="checkbox"/> Air inlet adapters & shutoff
Cooling	<ul style="list-style-type: none"> <li>• Radiator with guard</li> <li>• Coolant drain line with valve</li> <li>• Fan and belt guards</li> <li>• Cat® Extended Life Coolant*</li> </ul>	<input type="checkbox"/> Radiator duct flange <input type="checkbox"/> Jacket water heater
Exhaust	<ul style="list-style-type: none"> <li>• Dry exhaust manifold</li> <li>• Flanged faced outlets</li> </ul>	<input type="checkbox"/> Mufflers and Silencers <input type="checkbox"/> Stainless steel exhaust flex fittings <input type="checkbox"/> Elbows, flanges, expanders & Y adapters
Fuel	<ul style="list-style-type: none"> <li>• Secondary fuel filters</li> <li>• Fuel priming pump</li> <li>• Flexible fuel lines</li> <li>• Fuel cooler*</li> </ul>	<input type="checkbox"/> Fuel cooler <input type="checkbox"/> Water separator
Generator	<ul style="list-style-type: none"> <li>• Class H insulation</li> <li>• Cat digital voltage regulator (CDVR) with kVAR/PF control, 3-phase sensing</li> <li>• Reactive droop</li> </ul>	<input type="checkbox"/> Oversize & premium generators <input type="checkbox"/> Winding temperature detectors <input type="checkbox"/> Bearing temperature detectors <input type="checkbox"/> Anti-condensation heaters
Power Termination	<ul style="list-style-type: none"> <li>• Bus bar (IEC mechanical lug holes)</li> <li>• Top cable entry</li> </ul>	<input type="checkbox"/> Circuit breakers, IEC compliant, 3 or 4 pole with shunt trip (low voltage only), choice of trip units, manual or electrically operated <input type="checkbox"/> Bottom cable entry <input type="checkbox"/> Power terminations can be located on the right, left and/or rear as an option.
Governor	<ul style="list-style-type: none"> <li>• ADEM™ 3</li> </ul>	<input type="checkbox"/> Load share module
Control Panels	<ul style="list-style-type: none"> <li>• EMCP 3.1</li> <li>• User Interface panel (UIP) - wall mounted</li> <li>• AC &amp; DC customer wiring area (right side)</li> <li>• Emergency top pushbutton</li> </ul>	<input type="checkbox"/> EMCP 3.2 ... <input type="checkbox"/> EMCP 3.3 <input type="checkbox"/> Option for right or left mount UIP <input type="checkbox"/> Local & remote annunciator modules <input type="checkbox"/> Digital I/O Module <input type="checkbox"/> Generator temperature monitoring & protection <input type="checkbox"/> Remote monitoring software
Lube	<ul style="list-style-type: none"> <li>• Lubricating oil and filter</li> <li>• Oil drain line with valves</li> <li>• Fumes disposal</li> <li>• Gear type lube oil pump</li> </ul>	<input type="checkbox"/> Oil level regulator <input type="checkbox"/> Deep sump oil pan <input type="checkbox"/> Electric & air prelube pumps <input type="checkbox"/> Manual prelube with sump pump <input type="checkbox"/> Duplex oil filter
Mounting	<ul style="list-style-type: none"> <li>• Rails - Engine / generator / radiator mounting</li> <li>• Rubber anti-vibration mounts (shipped loose)</li> </ul>	<input type="checkbox"/> Isolator removal <input type="checkbox"/> Spring-type vibration isolator (shipped loose) <input type="checkbox"/> IBC Isolator
Starting/Charging	<ul style="list-style-type: none"> <li>• 24 volt starting motor(s)</li> <li>• Batteries with rack and cables</li> <li>• Battery disconnect switch</li> </ul>	<input type="checkbox"/> Battery chargers (5 or 10 amp) <input type="checkbox"/> 45 amp charging alternator <input type="checkbox"/> Oversize batteries <input type="checkbox"/> Ether starting aids <input type="checkbox"/> Heavy duty starting motors <input type="checkbox"/> Barring device (manual)
General	<ul style="list-style-type: none"> <li>• Right-hand service</li> <li>• Paint - Caterpillar Yellow except rails and radiators are gloss black</li> <li>• SAE standard rotation</li> <li>• Flywheel and flywheel housing - SAE No. 00</li> </ul>	<input type="checkbox"/> CSA certification <input type="checkbox"/> CE Certificate of Conformance <input type="checkbox"/> Seismic Certification per Applicable Building Codes: IBC 2000, IBC 2003, IBC 2006, IBC 2009, CBC 2007 * Not included with packages without radiators

# STANDBY 1400 kW 1750 kVA

50 Hz 1500 rpm 400 Volts



## SPECIFICATIONS

### CAT GENERATOR

Caterpillar Generator  
Frame size..... 1602  
Excitation..... IE  
Pitch..... 0.6667  
Number of poles..... 4  
Number of bearings..... 2  
Number of Leads..... 006  
Insulation..... UL 1446 Recognized Class H with tropicalization and antiabrasion  
Alignment..... Closed Coupled  
Overspeed capability - % of rated..... 150  
Wave form..... 002.00  
Paralleling kit/Droop transformer..... Standard  
Voltage regulator. 3 Phase sensing with selectable volts/Hz  
Voltage regulation..... Less than +/- 1/2% (steady state)  
Less than +/- 1% (no load to full load)  
Telephone Influence Factor..... Less than 50  
Harmonic distortion..... Less than 5%

### CAT DIESEL ENGINE

3512B HD, 4-stroke-cycle watercooled diesel  
Bore - mm..... 170.00 mm (6.69 in)  
Stroke - mm..... 215.00 mm (8.46 in)  
Displacement - L..... 58.56 L (3573.55 in<sup>3</sup>)  
Compression ratio..... 15.5:1  
Aspiration..... TA  
Fuel system..... Electronic unit injection  
Governor type..... ADEM3

### CAT EMCP SERIES CONTROLS

- EMCP 3.1 (Standard)
- EMCP 3.2 / EMCP 3.3 (Option)
- Single location customer connection point
- True RMS AC metering, 3-phase
- Controls:
  - Run / Auto / Stop control
  - Speed Adjust
  - Voltage Adjust
  - Emergency Stop Pushbutton
  - Engine cycle crank
- Digital Indication for:
  - RPM
  - Operating hours
  - Oil pressure
  - Coolant temperature
  - System DC Volts
  - L-L volts, L-N volts, phase amps, Hz
  - kW, kVA, kVAR, kW-hr, %kW, PF (EMCP 3.2 / 3.3)
- Shutdowns with common indicating light for:
  - Low oil pressure
  - High coolant temperature
  - Low coolant level
  - Overspeed
  - Emergency stop
  - Failure to start (over crank)
- Programmable protective relaying functions: (EMCP 3.2 & 3.3)
  - Under and over voltage
  - Under and over frequency
  - Overcurrent (time and inverse time)
  - Overcurrent
- Reverse power (3.3)
- MODBUS isolated data link, RS-485 half-duplex (EMCP 3.2 & 3.3)
- Options
  - Vandal door
  - Local annunciator module
  - Remote annunciator module
  - Input / Output module
  - RTD / Thermocouple modules
  - Monitoring software

**TECHNICAL DATA**

Open Generator Set - - 1500 rpm/50 Hz/400 Volts	DM8239	
<b>Low Emissions</b>		
<b>Generator Set Package Performance</b> Genset Power rating @ 0.8 pf Genset Power rating with fan	1750 kVA 1400 kW	
<b>Coolant to aftercooler</b> Coolant to aftercooler temp max	30 ° C	86 ° F
<b>Fuel Consumption</b> 100% load with fan 75% load with fan 50% load with fan	371.7 L/hr 280.4 L/hr 193.2 L/hr	98.2 Gal/hr 74.1 Gal/hr 51.0 Gal/hr
<b>Cooling System<sup>1</sup></b> Air flow restriction (system) Engine Coolant capacity with radiator/exp. tank Engine coolant capacity Radiator coolant capacity	0.12 kPa 305.8 L 156.8 L 149.0 L	0.48 in. water 80.8 gal 41.4 gal 39.4 gal
<b>Inlet Air</b> Combustion air inlet flow rate	128.1 m <sup>3</sup> /min	4523.8 cfm
<b>Exhaust System</b> Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	444.0 ° C 323.0 m <sup>3</sup> /min 203.2 mm 6.7 kPa	831.2 ° F 11406.6 cfm 8.0 in 26.9 in. water
<b>Heat Rejection</b> Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to aftercooler Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	514 kW 1383 kW 417 kW 121 kW 78.4 kW	29231 Btu/min 78651 Btu/min 23715 Btu/min 6881 Btu/min 4458.6 Btu/min
<b>Alternator<sup>2</sup></b> Motor starting capability @ 30% voltage dip Frame Temperature Rise	4266 skVA 1602 125 ° C	225 ° F
<b>Lube System</b> Sump refill with filter	310.4 L	82.0 gal
<b>Emissions (Nominal)<sup>3</sup></b> NOx mg/nm <sup>3</sup> CO mg/nm <sup>3</sup> HC mg/nm <sup>3</sup> PM mg/nm <sup>3</sup>	1709.3 mg/nm <sup>3</sup> 317.9 mg/nm <sup>3</sup> 72.5 mg/nm <sup>3</sup> 31 mg/nm <sup>3</sup>	

<sup>1</sup> For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.

<sup>2</sup> Generator temperature rise is based on a 40° C (104° F) ambient per NEMA MG1-32.

<sup>3</sup> Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

# STANDBY 1400 e kW 1750 kVA

50 Hz 1500 rpm 400 Volts



## RATING DEFINITIONS AND CONDITIONS

---

**Meets or Exceeds International Specifications:** AS1359, CSA, IEC60034-1, ISO3046, ISO8528, NEMA MG 1-22, NEMA MG 1-33, UL508A, 72/23/EEC, 98/37/EC, 2004/108/EC

**Standby** - Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year. Standby power in accordance with ISO8528. Fuel stop power in accordance with ISO3046. Standby ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature just below the shutdown temperature.

**Ratings** are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions. **Fuel rates** are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

# STANDBY 1400 kW 1750 kVA

50 Hz 1500 rpm 400 Volts



## DIMENSIONS

---

Package Dimensions		
Length	5468.8 mm	215.31 in
Width	2093.0 mm	82.4 in
Height	2367.2 mm	93.2 in
Weight	12 642 kg	27,871 lb

NOTE: For reference only - do not use for installation design. Please contact your local dealer for exact weight and dimensions. (General Dimension Drawing #2882685).

Performance No.: DM8239

Feature Code: 512DE6Y

Gen. Arr. Number: 2523838

Source: European Sourced

November 02 2010

16296102

[www.CAT-ElectricPower.com](http://www.CAT-ElectricPower.com)

© 2010 Caterpillar  
All rights reserved.

Materials and specifications are subject to change without notice.  
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, SAFETY.CAT.COM their respective logos, "Caterpillar Yellow," and the POWER EDGE trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.