



Cat screeds provide excellent durability, easy adjustment, and simple maintenance. Simple heating element replacement and machined screed frames facilitate quick service and reduce operating costs.

MODEL	PAVER COMPATIBILITY	WEIGHT	STANDARD PAVING RANGE	MAXIMUM PAVING WIDTH	MINIMUM PAVING WIDTH
SE34 V Vibratory	AP300, AP355	1400 kg (3,086 lb)	1.75 - 3.42 m (5 ft 9 in - 11 ft 2 in)	4.6 m (15 ft 1 in)	700 mm (27.5 in)
SE34 VT Tamper	AP300, AP355	1450 kg (3,196 lb)	1.75 - 3.42 m (5 ft 9 in - 11 ft 2 in)	4.6 m (15 ft 1 in)	700 mm (27.5 in)
SE47 FM Front-Mount (4B5)	AP400, AP455, AP500, AP555	2755 kg (6,073 lb)	2.44 m - 4.7 m (8 ft - 15 ft 6 in)	6.25 m (20 ft 6 in)	1.22 m (4 ft)
SE47 FM Front-Mount (411)	AP600, AP655	2812 kg (6,200 lb)			
SE47 V Vibratory	AP400, AP455, AP500, AP555	2654 kg (5,850 lb)	2.44 m - 4.7 m (8 ft - 15 ft 6 in)	6.1 m (20 ft)	1.22 m (4 ft)
SE47 VT Tamper	AP400, AP455, AP455 Steel Track, AP500, AP555, AP555 Steel Track	3050 kg (6,724 lb)	2.4 m - 4.68 m (7 ft 10 in - 15 ft 4 in)	6 m (19 ft 8 in)	1.18 m (3 ft 10 in)
SE50 V Vibratory	AP600, AP655	3284 kg (7,239 lb)	2.55 - 5 m (8 ft 4 in - 16 ft 4 in)	6.5 m (21 ft 4 in)	1.32 m (4 ft 4 in)
SE50 VT Tamper (A42)	AP500, AP555, AP555 Steel Track	3129 kg (6,898 lb)	2.55 - 5 m (8 ft 4 in - 16 ft 4 in)	7.64 m (25 ft)	1.32 m (4 ft 4 in)
SE50 VT Tamper (B86)	AP600, AP655, AP655 L	3295 kg (7,264 lb)			
SE60 FM Front-Mount	AP600, AP655, AP1000, AP1055	3538 kg (7,800 lb)	3.05 - 5.94 m (10 ft - 19 ft 6 in)	7.77 m (25 ft 6 in)	1.83 m (6 ft)
SE60 V Vibratory	AP600, AP655, AP1000, AP1055	3550 kg (7,826 lb)	3 - 6 m (9 ft 10 in - 19 ft 6 in)	7.65 m (25 ft)	1.78 m (5 ft 10 in)
SE60 V XW Vibratory	AP655, AP1000, AP1055	4225 kg (9,314 lb)	3 - 6 m (9 ft 10 in - 19 ft 6 in)	10 m (33 ft)	1.78 m (5 ft 10 in)
SE60 VT XW Tamper	AP655, AP655 L, AP1000, AP1055	4660 kg (10,273 lb)	3 - 6 m (9 ft 10 in - 19 ft 6 in)	10 m (33 ft)	1.78 m (5 ft 10 in)

Weights are approximate. Options may vary by region. Some models are not offered in all areas. For availability and configurations, please contact your local Cat dealer or visit www.cat.com.